Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of the Claims

- 1-36. (Cancelled).
- 37. (Previously presented) An electrosurgical instrument having an end effector, the end effector configured to simultaneously provide radio frequency power and a fluid to treat tissue, the power sufficient to cause a dimensional change of the tissue, the end effector comprising:
 - at least one electrode:
 - at least one fluid outlet; and
 - a dimensional change sensor to detect the dimensional change of the tissue.
- 38. (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor is configured to move relative to the dimensional change of the tissue.
- 39. (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor is configured to provide feedback to vary the radio frequency power according to the dimensional change of the tissue.
- 40. (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor is configured to provide feedback to treat the tissue to a predetermined dimensional change.

- (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor is configured to provide feedback to measure the dimensional change.
- 42. (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor is operatively associated with a device to provide a measurement of the dimensional change.
- (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor is operatively associated with means to provide a measurement of the dimensional change.
- (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor comprises a contact sensor.
- 45. (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor comprises a shrinkage sensor; and the dimension change of the tissue comprises a shrinkage of the tissue.
- 46. (Previously presented) The electrosurgical instrument of claim 45 wherein: the shrinkage sensor is configured to move relative to the shrinkage of the tissue.
- 47. (Previously presented) The electrosurgical instrument of claim 45 wherein: the shrinkage sensor is configured to provide feedback to vary the radio frequency power according to the shrinkage of the tissue.

- 48. (Previously presented) The electrosurgical instrument of claim 45 wherein: the shrinkage sensor is configured to provide feedback to treat the tissue to a predetermined shrinkage.
- (Previously presented) The electrosurgical instrument of claim 45 wherein:
 the shrinkage sensor is configured to provide feedback to measure the shrinkage.
- (Previously presented) The electrosurgical instrument of claim 45 wherein:
 the shrinkage sensor is operatively associated with a device to provide a measurement of the shrinkage.
- (Previously presented) The electrosurgical instrument of claim 45 wherein:
 the shrinkage sensor is operatively associated with means to provide a measurement of the shrinkage.
- (Withdrawn) The electrosurgical instrument of claim 37 further comprising:
 a monopolar electrosurgical instrument.
- (Previously presented) The electrosurgical instrument of claim 37 further comprising:
 a bipolar electrosurgical instrument.
- 54. (Previously presented) The electrosurgical instrument of claim 37 wherein: the at least one fluid outlet is positioned to provide the fluid onto the at least one electrode.
- 55. (Previously presented) The electrosurgical instrument of claim 37 wherein: the at least one fluid outlet is at least partially defined by the at least one electrode.

- 56. (Previously presented) The electrosurgical instrument of claim 37 wherein: the at least one fluid outlet is at least partially defined by a hole in the at least one electrode.
- 57. (Previously presented) The electrosurgical instrument of claim 37 wherein: the at least one fluid outlet is configured to provide the fluid to wet the at least one electrode.
- (Previously presented) The electrosurgical instrument of claim 37 wherein:
 the at least one electrode comprises a plurality of electrodes.
- (Previously presented) The electrosurgical instrument of claim 37 wherein: the at least one fluid outlet comprises a plurality of fluid outlets.
- 60. (Previously presented) The electrosurgical instrument of claim 37 wherein: the at least one electrode comprises a first electrode and a second electrode; and the at least one fluid outlet comprises a first fluid outlet and a second fluid outlet.
- (Previously presented) The electrosurgical instrument of claim 60 wherein:
 the first fluid outlet is positioned to provide the fluid onto the first electrode; and
 the second fluid outlet is positioned to provide the fluid onto the second electrode.
- 62. (Previously presented) The electrosurgical instrument of claim 60 wherein: the first fluid outlet is configured to provide the fluid to wet the first electrode; and the second fluid outlet is configured to provide the fluid to wet the second electrode.

- (Previously presented) The electrosurgical instrument of claim 37 wherein: the end effector comprises a jaw.
- 64. (Previously presented) The electrosurgical instrument of claim 37 wherein: the end effector comprises a forceps.
- 65. (Previously presented) The electrosurgical instrument of claim 37 wherein: the dimensional change sensor comprises a clamp structure to grasp the tissue.